

Product Datasheet model astrospec 2.0 9164 141

**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

**Product
characteristics**

- Flexible 2K side arms and inclination
- Ventilation with labyrinth seal helps improve climate around the eyes
- Panoramic polycarbonate lens with integrated side protectors for optimum coverage of the eyes
- Folds flat
- New filter technology
- Perfect colour recognition conforms to uvex grey sunglare filters
- UV and IR radiation protection
- Minimises damage from welding sparks

Technical details

Frame

Material
Colour

Front piece

PC+TPU
black

Material
Colour

Side piece

POM
grey

Material
Colour

Temple

PC+TPU/TPE
black-green

Manufacturer's ID code
Applicable EN norm
Low-energy impact
Resistance to high
speed particles at
extremes of temperat.
Conformity symbol


Marking

W
166
F (45 m/s)
T
CE

Lens

Material
Thickness
Coating
Colour
UV protection
IR protection

PC
2,2 mm
uvex infradur plus
grey
UV 400
Fulfilled

Filter	Marking 1,7 (DIN EN 169)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Resistance to high speed particles at extremes of temperat.	T
Surface resistance to fine particles	K
Antifog	N
Conformity symbol	CE
Factory symbol	
Miscellaneous	
Weight	37 g
Packing	5 spectacles per box 160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 169
PPE Category	Category II