

SAFETY FOOTWEAR

26.08.19 SBU-F-PGM-PM

Product data sheet uvex 1 6566.7-9 S2 SRC





UVEX ARBEITSSCHUTZ GmbH, Würzburger Str. 181-189, D-90766 Fürth

General features	 Sporty, multifunctional safety shoe Especially lightweight and flexible Breathable high-tech micro velour upper material Suitable for people allergic to chrome. Made from synthetic materials All sole materials are free of silicones, plasticisers and other paint wetting impairment substances BOA® Fit System for a fast, effortless, precision fit
Protection features	 100% metal-free uvex xenova® toe cap - compact design, anatomical shape, good lateral stability, no thermal conductivity properties Meets the ESD specification with volume resistance less than 35 megaohms
Comfort features	 Outstanding wearer comfort results from a newly developed last and climate-optimised, breathable materials Virtually seamless design to eliminate pressure points Removable comfort insole, antistatic, with moisture control system and additional shock absorption in the heel and at the front of the foot Distance mesh lining provides optimum breathability Soft padded collar and tongue
Outsole	PUR outsole, non-marking

Rev. St. 1 Datum: 19.05.2015 Seite 1 von 2

	 Ergonomically designed tread Multi-layer-shock absorption system using dual density polyurethane for walking comfort Excellent slip resistance Self-cleaning tread Resistant to oil and petrol
Certificates	Certified with uvex medicare for individual, orthopaedic inlay soles and individual adjustments of the sole unit such as overall increase, inside and outside increase and other solutions.
Areas of application	Light applications
Technical data	Artno. 6566.7 .8 .9 Width 10 11 12 Standard EN ISO 20345:2011 S2 SRC Size 35 – 52
Accessories	 uvex 1 comfortable climatic insole (article no.: 9534.7-9) Provides the foot with exceptional, full-surface shock absorption and ensures comfort in high-strain zones Ultra breathable and moisture-absorbing materials Shock absorption zones that assist natural movement Non-irritating, comfortable surface structure

Rev. St. 1 Datum: 19.05.2015 Seite 2 von 2